



SAFETY DATA SHEET
(in accordance with Regulation (EU) 2015/830)
**FASTCOAT Rust Inhibiting
Primer**



Version: 36

Page 1 of 11
Print date: 24/01/2018

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: FASTCOAT Rust Inhibiting Primer
Product Code: P363

1.2 Relevant identified uses of the mixture and uses advised against.

Coating

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **Liquid Roofing Systems Ltd**
Address: Prees Green
City: Shropshire
Telephone: 01948 841 877
Fax: 01948 841 854
E-mail: info@lrs-systems.co.uk
Web: lrs-systems.co.uk

1.4 Emergency telephone number: 01948 841 877 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if inhaled.

Eye Irrit. 2 : Causes serious eye irritation.

Flam. Liq. 2 : Highly flammable liquid and vapour.

Resp. Sens. 1 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Irrit. 2 : Causes skin irritation.

Skin Sens. 1 : May cause an allergic skin reaction.

STOT SE 3 : May cause respiratory irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

| | |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |

P statements:

| | |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
|------|--|



SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FASTCOAT Rust Inhibiting Primer

Version: 36



Page 2 of 11
Print date: 24/01/2018

| | |
|-----------|--|
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P284 | [In case of inadequate ventilation] wear respiratory protection. |
| P321 | Specific treatment. |
| P342+P311 | If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... |
| P370+P378 | In case of fire: Use dry powder or dry sand to extinguish |

EUH statements:

EUH204 Contains isocyanates. May produce an allergic reaction.

Contains:

4-isocyanatosulphonyltoluene, tosyl isocyanate
xylene (Mixture of isomers)
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate
o-(p-isocyanatobenzyl)phenyl isocyanate, diphenylmethane-2,4'-diisocyanate
Polymeric diphenylmethane diisocyanate

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

| Identifiers | Name | Concentrate | (*)Classification - Regulation (EC) No 1272/2008 | |
|---|--|-------------|--|--|
| | | | Classification | specific concentration limit |
| Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX | [1] xylene (Mixture of isomers) | 6 - 10 % | Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 | - |
| Index No: 615-005-00-9 CAS No: 101-68-8 EC No: 202-966-0 Registration No: 01-2119457014-47-XXXX | 4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate | 1 - 5 % | Acute Tox. 4 *, H332 - Carc. 2, H351 - Eye Irrit. 2, H319 - Resp. Sens. 1, H334 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 - STOT RE 2 *, H373** - STOT SE 3, H335 | Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 % Resp. Sens. 1, H334: C ≥ 0,1 % STOT SE 3, H335: C ≥ 5 % |
| Index No: 615-005-00-9 CAS No: 5873-54-1 EC No: 227-534-9 Registration No: 01-2119480143-45-XXXX | o-(p-isocyanatobenzyl)phenyl isocyanate, diphenylmethane-2,4'-diisocyanate | 1 - 5 % | Acute Tox. 4 *, H332 - Carc. 2, H351 - Eye Irrit. 2, H319 - Resp. Sens. 1, H334 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 - STOT RE 2 *, H373** - STOT SE 3, H335 | Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 % Resp. Sens. 1, H334: C ≥ 0,1 % STOT SE 3, H335: C ≥ 5 % |

-Continued on next page.-



SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FASTCOAT Rust Inhibiting Primer



Version: 36

Page 3 of 11
Print date: 24/01/2018

| | | | | |
|---|--|----------|--|---|
| CAS No: 9016-87-9 | Polymeric diphenylmethane diisocyanate | 1 - 10 % | Carc. 2, H351 - Eye Irrit. 2, H319 - Resp. Sens. 1, H334 - Skin Irrit. 2, H315 - STOT RE 2, H373 - STOT SE 3, H335 | - |
| Index No: 615-012-00-7 CAS No: 4083-64-1 EC No: 223-810-8 | 4-isocyanatosulphonyltoluene, tosyl isocyanate | 1 - 5 % | Eye Irrit. 2, H319 - Resp. Sens. 1, H334 - Skin Irrit. 2, H315 - STOT SE 3, H335 | Eye Irrit., H319: C ≥ 5 % STOT SE 3, H335: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 % |

(*)The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

*,** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

-Continued on next page.-



SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FASTCOAT Rust Inhibiting Primer

Version: 36



Page 4 of 11
Print date: 24/01/2018

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.



SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FASTCOAT Rust Inhibiting Primer

Version: 36



Page 5 of 11
Print date: 24/01/2018

Work exposure limit for:

| Name | CAS No. | Country | Limit value | ppm | mg/m ³ |
|-----------------------------|-----------|--------------------|--------------------|------------|-------------------|
| xylene (Mixture of isomers) | 1330-20-7 | European Union [1] | Eight hours | 50 (skin) | 221 (skin) |
| | | | Short term | 100 (skin) | 442 (skin) |
| | | United Kingdom [2] | Eight hours | 50 | 220 |
| | | | Short term | 100 | 441 |

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

| Name | DNEL/DMEL | Type | Value |
|--|-------------------|---|------------------------------|
| xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7 | DNEL (Workers) | Inhalation, Long-term, Systemic effects | 77 (mg/m ³) |
| 4,4'-methylenediphenyl diisocyanate,diphenylmethane-4,4'-diisocyanate CAS No: 101-68-8 EC No: 202-966-0 | DNEL (Workers) | Inhalation, Long-term, Local effects | 0,05 (mg/m ³) |
| | DNEL (Workers) | Inhalation, Long-term, Systemic effects | 0,05 (mg/m ³) |
| o-(p-isocyanatobenzyl)phenyl isocyanate,diphenylmethane-2,4'-diisocyanate CAS No: 5873-54-1 EC No: 227-534-9 | DNEL (Workers) | Inhalation, Long-term, Local effects | 0,05 (mg/m ³) |
| | DNEL (Workers) | Inhalation, Long-term, Systemic effects | 0,05 (mg/m ³) |



DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

| | | | |
|---|---|---------------------------------|---|
| Concentration: | 100 % | | |
| Uses: | Coating | | |
| Breathing protection: | | | |
| PPE: | Filter mask for protection against gases and particles. | |  |
| Characteristics: | «CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight. | | |
| CEN standards: | EN 136, EN 140, EN 405 | | |
| Maintenance: | Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. | | |
| Observations: | Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer. | | |
| Filter Type needed: | A2 | | |
| Hand protection: | | | |
| PPE: | Protective gloves against chemicals. | |  |
| Characteristics: | «CE» marking, category III. | | |
| CEN standards: | EN 374-1, En 374-2, EN 374-3, EN 420 | | |
| Maintenance: | Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. | | |
| Observations: | Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. | | |
| Material: | PVC (polyvinyl chloride) | Breakthrough time (min.): > 480 | Material thickness (mm): 0,35 |
| Eye protection: | | | |
| If the product is handled correctly, no individual protection equipment is necessary. | | | |
| Skin protection: | | | |
| PPE: | Protective clothing. | | |

-Continued on next page.-



SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FASTCOAT Rust Inhibiting Primer

Version: 36



Page 6 of 11
Print date: 24/01/2018

| | |
|------------------|--|
| Characteristics: | «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. |
| CEN standards: | EN 340 |
| Maintenance: | In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. |
| Observations: | The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. |
| PPE: | Work footwear. |
| Characteristics: | «CE» marking, category II. |
| CEN standards: | EN ISO 13287, EN 20347 |
| Maintenance: | This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. |
| Observations: | Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour

Colour: gray

Odour: typical

Odour threshold: not determined

pH: n.a.

Melting point: not determined °C

Boiling Point: >100 °C

Flash point: >21 °C

Evaporation rate: not determined

Inflammability (solid, gas): flammable

Lower Explosive Limit: 1%

Upper Explosive Limit: 7%

Vapour pressure: not determined

Vapour density: not determined

Relative density: 2.25 g/cm³

Solubility: organic solvents

Liposolubility: not determined

Hydrosolubility: non soluble

Partition coefficient (n-octanol/water): not determined

Auto-ignition temperature: not determined °C

Decomposition temperature: not determined °C

Viscosity: 1000-3000

Explosive properties: not determined

Oxidizing properties: not determined

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: not determined

Blink: not determined

Kinematic viscosity: not determined

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.



SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FASTCOAT Rust Inhibiting Primer

Version: 36



Page 7 of 11
Print date: 24/01/2018

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Exposure to concentrations of solvent fumes above the work exposure limit can have negative effects (for example, irritation of the mucous membranes and respiratory system, adverse effects on the kidneys, liver, and the central nervous system). Among the symptoms are headaches, vertigo, fatigue, muscular weakness, drowsiness, and in extreme cases, unconsciousness.

Based on the properties of isocyanates and taking into account existing technical data on similar products, it appears that this product may cause irritation and / or acute awareness of the respiratory system, leading to an asthmatic condition, a wheezing and chest pressure. Therefore, sensitized individuals may show asthmatic symptoms when exposed to atmospheres containing concentrations below the level of exposure. Repeated exposure can lead to chronic respiratory diseases.

Toxicological information about the substances present in the composition.

| Name | Acute toxicity | | | |
|---|----------------|------|---------------|--|
| | Type | Test | Kind | Value |
| xylene (Mixture of isomers) | Oral | LD50 | Rata/Rat | 4300 mg/kg bw [1] |
| | | | | [1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956 |
| CAS No: 1330-20-7 EC No: 215-535-7 | Dermal | LD50 | Rabbit/Conejo | > 1700 mg/kg bw [1] |
| | | | | [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974 |
| | Inhalation | LC50 | Rat/Rata | 21,7 mg/l/4 h [1] |
| | | | | [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974 |

a) acute toxicity;

Product classified:

Acute toxicity (Inhalation), Category 4: Harmful if inhaled.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 3.245 mg/kg

ATE (Inhalation) = 17 mg/l/4 h (Fumes)

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Respiratory sensitiser, Category 1: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitiser, Category 1: May cause an allergic skin reaction.



SAFETY DATA SHEET
(in accordance with Regulation (EU) 2015/830)
**FASTCOAT Rust Inhibiting
Primer**



Version: 36

Page 8 of 11
Print date: 24/01/2018

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Product classified:
Carcinogen, Category 2: Suspected of causing cancer.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;
Based on available data, the classification criteria are not met.

j) aspiration hazard;
Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

| Name | Ecotoxicity | | | |
|--|-----------------------|------|------------|---|
| | Type | Test | Kind | Value |
| xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7 | Fish | LC50 | Fish/Pez | 15,7 mg/l (96 h) [1] [1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212 |
| | Aquatic invertebrates | LC50 | Crustacean | 8,5 mg/l (48 h) [1] [1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p |
| | Aquatic plants | | | |

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.



SAFETY DATA SHEET
(in accordance with Regulation (EU) 2015/830)
**FASTCOAT Rust Inhibiting
Primer**



Version: 36

Page 9 of 11
Print date: 24/01/2018

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number.

UN No: UN1263

14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT, 3, PG III, (D/E)

IMDG: UN 1263, PAINT, 3, PG III (21°C)

ICAO: UN 1263, PAINT, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 3



Hazard number: 30

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E

Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

P363-PU ZN Primer

Version: 36

Revision date: 03/05/2017

Page 10 of 11

Print date: 24/01/2018

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): Primer (Wash primer)

Phase I* (from 01/01/2007): 780 g/l

Phase II* (from 01/01/2010): 780 g/l

(*) g/l ready to use

VOC content (p/p): 13,55 %

VOC content: 280 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

| | |
|------|--|
| H226 | Flammable liquid and vapour. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Classification codes:

Acute Tox. 4 [Dermal] : Acute toxicity (Dermal), Category 4
Acute Tox. 4 [Inhalation] : Acute toxicity (Inhalation), Category 4
Carc. 2 : Carcinogen, Category 2
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Resp. Sens. 1 : Respiratory sensitiser, Category 1
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

P363-PU ZN Primer

Version: 36

Revision date: 03/05/2017

Page 11 of 11

Print date: 24/01/2018

- considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.